



| <u>REF.</u> | <u>COD.</u> | | | | | | | | |
|-------------|-------------|----|------------|------------------------------|--|------------------------------|---------------------------------------|--|--|
| 1 | B000028A12 | 43 | C450180A01 | Codice A740000A10 | DATI TECNICI | POTENZA ACUSTICA | VIBRAZIONI PRODOTTE | | |
| 2 | C440101A01 | 44 | B000028E02 | Modello M40 | Peso: 1720 gr. | DIRETTIVA 89/392 CEE | DIRETTIVA 89/392 CEE | | |
| 3 | C440103A01 | 45 | C620768A01 | Tipo Punto 92 | Dimensioni: 80-242-285 mm. | p/EN 12549 (1999) | ISO/FDIS 8662-11 (1999) | | |
| 4 | B000028C04 | 46 | B000023B02 | Lungh. min. 20 mm. | Consumo aria: 1,28 NI/colpo (6 bar) | UNI EN ISO 3744 (1997) | ah.w.3s= 2,6 (m/s²) | | |
| 5 | C450180A01 | 47 | D640707A01 | Lungh. max. 40 mm. | Pressione min.: 4,0 bar | LWA= 87,5 (dB) | | | |
| 6 | D440123A01 | 48 | B000028E14 | | Pressione max.: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 7 | C240160A01 | 49 | B000021C01 | Kode A740000A10 | TECHNISCHE DATEN | SCHALLEISTUNG | GERAETEBEZUGENER | | |
| 8 | B000020A06 | 50 | D730484A01 | Modello M40 | Gewicht: 1720 gr. | EWG RICHTLINIE 89/392 | VIBRATIONSWERT | | |
| 9 | C440181A01 | 51 | B000026A09 | Klammer Typ 92 | Abmessungen: 80-242-285 mm. | p/EN 12549 (1999) | EWG RICHTLINIE 89/392 | | |
| 10 | B000020A43 | 52 | B000028C05 | Min. Länge 20 mm. | Luftverbrauch: 1,28 NI/pro Schlag (6 bar) | UNI EN ISO 3744 (1997) | ISO/FDIS 8662-11 (1999) | | |
| 11 | D440202A01 | 53 | B000028B23 | Min. Länge 40 mm. | Min. Betriebsdruck: 4,0 bar | LWA= 87,5 (dB) | ah.w.3s= 2,6 (m/s²) | | |
| 12 | B000020A40 | 54 | C730681A01 | | Max. Betriebsdruck: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 13 | B000020A39 | 55 | C230661A01 | Code A740000A10 | TECHNICAL FEATURES | NOISE POWER | TOOL RELATED VIBRATION | | |
| 14 | D440204A01 | 56 | C740660A01 | Modello M40 | Weight: 1720 gr. | EEC DIRECTIVE 89/392 | VALUE | | |
| 15 | B000020A44 | 57 | C730540A05 | Staple type 92 | Dimensions: 80-242-285 mm. | p/EN 12549 (1999) | EEC DIRECTIVE 89/392 | | |
| 16 | B000023B05 | 58 | C730912A05 | Min. length 20 mm. | Air consumption: 1,28 NI/shot (6 bar) | UNI EN ISO 3744 (1997) | ISO/FDIS 8662-11 (1999) | | |
| 17 | B000020A52 | 59 | B000028A03 | Max. length 40 mm. | Min. working pressure: 4,0 bar | LWA= 87,5 (dB) | ah.w.3s= 2,6 (m/s²) | | |
| 18 | C440220A01 | 60 | C640822A01 | | Max working pressure: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 19 | C640225A09 | 61 | C620736A01 | Code A740000A10 | DONNEES TECHNIQUES | PUISSANCE ACOUSTIQUE | VALEUR DES VIBRATIONS | | |
| 20 | B000020A60 | 62 | D640735A01 | Modèle M40 | Poids: 1720 gr. | DIRECTIVE CEE 89/392 | PAR LA MACHINE | | |
| 21 | D440241A02 | 63 | C430401A02 | Agrafe type 92 | Dimensions: 80-242-285 mm. | p/EN 12549 (1999) | DIRECTIVE CEE 89/392 | | |
| 22 | B000020A40 | 64 | C640937A09 | Longueur min. 20 mm. | Consumation d'air: 1,28 NI/coup (6 bar) | UNI EN ISO 3744 (1997) | ISO/FDIS 8662-11 (1999) | | |
| 23 | C240244A01 | 65 | B000026A21 | Longueur max. 40 mm. | Pression de fonction min.: 4,0 bar | LWA= 87,5 (dB) | ah.w.3s= 2,6 (m/s²) | | |
| 24 | B000020B02 | 66 | B000021C01 | | Pression de fonction max.: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 25 | B000020B01 | 67 | C620948A05 | Código A740000A10 | DATOS TECNICOS | POTENCIA ACUSTICA | VIBRACION PRODUCIDA | | |
| 26 | B000020A02 | 68 | C430401A02 | Modello M40 | Peso: 1720 gr. | NORMATIVA 89/392 CEE | NORMATIVA 89/392 CEE | | |
| 27 | D450304A01 | 69 | C620949A01 | Grapa tipo 92 | Dimensiones: 80-242-285 mm. | p/EN 12549 (1999) | ISO/FDIS 8662-11 (1999) | | |
| 28 | B000020B11 | 70 | C620820A01 | Larghezza min. 20 mm. | Consumo de aire: 1,28 NI/dispazo (6 bar) | UNI EN ISO 3744 (1997) | ah.w.3s= 2,6 (m/s²) | | |
| 29 | B000020A02 | 71 | C620824A01 | Larghezza max. 40 mm. | Presion min.: 4,0 bar | LWA= 87,5 (dB) | | | |
| 30 | D740361A01 | 72 | C620842A01 | | Presion max.: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 31 | B000020A19 | 73 | C620884A01 | Código A740000A10 | CARACTERISTICAS TECNICAS | POTENCIA ACUSTICA | NIVEL DE VIBRACAO | | |
| 32 | B000020A19 | 74 | C620860A05 | Modello M40 | Peso: 1720 gr. | DIRETTIVA 89/392 CEE | DO PRODUTO | | |
| 33 | B000026A12 | 75 | D440123A01 | Tipo de agrafe 92 | Dimensões: 80-242-285 mm. | p/EN 12549 (1999) | DIRETTIVA 89/392 CEE | | |
| 34 | D750411A02 | 76 | D440202A01 | Largura min. 20 mm. | Consumo de ar.: 1,28 NI/dispazo (6 bar) | UNI EN ISO 3744 (1997) | ISO/FDIS 8662-11 (1999) | | |
| 35 | C450262A01 | 77 | D440204A01 | Largura max. 40 mm. | Pressão min.: 4,0 bar | LWA= 87,5 (dB) | ah.w.3s= 2,6 (m/s²) | | |
| 36 | B000020A42 | 78 | D640226A09 | | Pressão max.: 7,0 bar | LPA 60S 1M= 86,7 (dB) | | | |
| 37 | D450283A01 | 79 | D440241A02 | | | | | | |
| 38 | C740261A01 | 80 | D450304A01 | | | | | | |
| 39 | C730500A01 | 81 | D740361A01 | | | | | | |
| 40 | D750441A01 | 82 | D450283A01 | | | | | | |
| 41 | B000026A09 | | | | | | | | |
| 42 | B000028B13 | | | | | | | | |

B640040A01 O-Ring Kit

74010 A10101 0711